













Type	Appearance	Operating position		Model	Contact block		LED block										
					A contact	B contact	AC/DC voltage	AC voltage									
Long shark-head lever, extended	 <p>S2SRN-S2AR□</p> 	2-position, spring return		S2SRN-S2A□A(M)	1EA	—	—	—									
				S2SRN-S2A□2A(M)	2EA	—											
				S2SRN-S2A□B(M)	—	1EA											
				S2SRN-S2A□2B(M)	—	2EA											
		2-position, maintained		S2SRN-S4A□A(M)	1EA	—											
				S2SRN-S4A□2A(M)	2EA	—											
				S2SRN-S4A□B(M)	—	1EA											
				S2SRN-S4A□2B(M)	—	2EA											
		2-position, spring return		S2SRN-S2B□A(M)	1EA	—											
				S2SRN-S2B□2A(M)	2EA	—											
				S2SRN-S2B□B(M)	—	1EA											
				S2SRN-S2B□2B(M)	—	2EA											
		2-position, maintained		S2SRN-S4B□A(M)	1EA	—											
				S2SRN-S4B□2A(M)	2EA	—											
				S2SRN-S4B□B(M)	—	1EA											
				S2SRN-S4B□2B(M)	—	2EA											
		3-position, spring return two-way		S2SRN-S6□2A(M)	2EA	—											
				S2SRN-S6□2B(M)	—	2EA											
				S2SRN-S6□AB(M)	1EA	1EA											
		3-position, maintained		S2SRN-S8□2A(M)	2EA	—											
				S2SRN-S8□2B(M)	—	2EA											
				S2SRN-S8□AB(M)	1EA	1EA											
		3-position, spring return from right		S2SRN-SB□2A(M)	2EA	—											
				S2SRN-SB□2B(M)	—	2EA											
				S2SRN-SB□AB(M)	1EA	1EA											
		3-position, spring return from left		S2SRN-SD□2A(M)	2EA	—											
				S2SRN-SD□2B(M)	—	2EA											
				S2SRN-SD□AB(M)	1EA	1EA											
<p>※□ indicates color: W (white), R (red)</p> <p>※The (M) in the model name indicates modular type contacts. Models without (M) are singular types.</p> <p>※The control unit and contact blocks are sold separately. (control unit: bold letters, contact block: regular letters)</p> <p>※Connect up to 2 contact blocks. Connect the contact blocks only on the side slots. It will not operate if connected to the center slot.</p> <p>• Dimensions <span style="float: right;">(unit: mm)</span></p> <div style="display: flex; align-items: center;">   <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th>A</th> <th>B</th> </tr> </thead> <tbody> <tr> <td>Singular type contact</td> <td>48.5</td> <td>27.0</td> </tr> <tr> <td>Modular type contact</td> <td>46.5</td> <td>25.0</td> </tr> </tbody> </table> </div> <p style="text-align: center;">※For panel cut-out dimensions, please refer to page A-36.</p>										A	B	Singular type contact	48.5	27.0	Modular type contact	46.5	25.0
	A	B															
Singular type contact	48.5	27.0															
Modular type contact	46.5	25.0															